

Model 1.5 WC Monitor

Model 1.5 WC Monitor



Shown in natural cherry

The 1.5 WC is true reference quality system. that uses state of the art drive units including a new 1"-neodym™ silk dome tweeter and 5" cast, Quiet Cone™, woofer. Its enclosure features rigid MDF construction and 3/4" thick front panel. A minimum phase, pure polypropylene, crossover optimizes integration of woofer and tweeter frequency response with less than 2 db variation.

Truly a speaker system for those seeking the very best in a small format, the 1.5 WC has excellent tonality, pinpoint imaging and wide sound staging.

Specifications

<i>Woofer ---</i>	<i>5" Wool Carbon with cast frame</i>
<i>Tweeter --</i>	<i>1" Neodym™ silk dome</i>
<i>Crossover</i>	<i>2.5khz minimum phase with HQ components</i>
<i>Loading</i>	<i>Sealed</i>
<i>Freq. Response -</i>	<i>55hz – 20 khz</i>
<i>Sensitivity</i>	<i>- 88 db. at 1 w 1 meter</i>
<i>Power Min-Max</i>	<i>20- 150 rms.</i>
<i>Impedance</i>	<i>5 ohms</i>
<i>Size</i>	<i>6.25" w x 9.8 "h x 6" d</i>
<i>Finishes</i>	<i>Real Wood Maple, Oak, Cherry</i>



Source Technologies 701 Nutmeg Road N.South Windsor, Conn. 06074
(860) 528 2892 , www.sourcetechnologies.com